

HEADSET BLUETOOTH

Users Manual

Declerance of Conformity

A-KABEL AS, Postbox 64, 2151 Årnes, Noway
hereby declares:

That AK6591 and AK6592 are manufactured in accordance with the harmonized standards
EN 352-3:2002 and EN352-1:2002 to Directive 89/686/EEC.

The headsets are tested according to EN 352-3:2002 and EN352-1:2002.
EC type examination certificate no. 26045KRS01, issued by Notified Body No. 0403:
Finnish Institute of Occupational Health,
Work Environment Development, Protection and Product Safety.
Topeliuskentkatu 41 aA,
00250 Helsinki
Finland

Årnes, 01.07.06

Per Ivar Engen
Managing Director

WARNING:

To re-charge the batteries, use only the original charger enclosed.
DO NOT use non re-chargeable batteries together with the charger!
It is normal that re-charging will take 6- 8 hours.

Manufactured by:

A-KABEL AS

Postboks 64, 2151 ÅRNES, NORWAY

Phone No.: +47 63 91 28 20 Fax No.: +47 63 91 28 30

E-Mail: engen@a-kabel.no



AK6592



AK6591

USER INFORMATION AK6591 and AK6592

This headset is made in two versions.

Helmet attachment; AK6591, and headband; AK6592.

Helmet attachment (AK6591)

Warning: The helmet attachment is adjustable from medium size to large size, complying with EN 352-1.

Fit the headset to the helmet by pressing the flat blade part of the attachment into the slot attachment brackets on the helmet. You should hear a “click” when the attachments are in the right position. The cup with the microphone should be placed to the left side of the helmet with the microphone facing forward. Put the helmet on top of your head and adjust the cups by sliding them up and down on the stainless steel rods on the helmet attachment to make them fit perfectly over the ears. When not working in noisy areas the cups can be placed in a resting position by pulling them straight out (away) your head. You will then hear a click and the cups will stay in a position about 10-15 mm. apart from the ears. You will also be able to swing the cups backwards and up to a resting position on the helmet body. The cups will fit back in exactly the same position when you press them back against the ears will hear a click. The helmet attachments will fit to following helmets: Peltor G22, OBX Iris and Balance.

Headband (AK6592)

Warning: The headband is adjustable from small size to medium size and large size, complying with EN 352-1.

Adjust the headband by sliding the cups up and down on the stainless steel rods on the headband while you assure that the head band is resting on the top of the head.

General instructions

The headband force is pre-adjusted from the factory to meet the requirements in the EEC Directives for PPE.

Medium size range ear-muffs will fit the majority of wearers. Small size range and large size range ear-muffs are designed to fit wearers for whom medium size range ear-muffs are not suitable.

The ear-muffs shall be worn at all times in noisy environments. Hair, beard and wearing of glasses can affect the acoustic performance of the ear-muffs. The ear-muffs shall be placed directly over the ear. Ensure that the cushions will fit tight to the skin all around the ears.

Maintenance

Keep the headset dry and clean by using a clean cloth. If necessary, moisten a cloth with water and ordinary soap. Alcohol may be used to disinfect the headset. Do not spill liquid on the attenuation foam inserts or the inner parts of the headset. The earmuffs shall be regularly inspected for damages and pollution. The ear cushions (PVC and PUR) and the visible attenuation foam (PUR) can easily be replaced with a hygienic kit, order no. AK6501. The fitting of the hygienic covers to the cushions may affect the acoustic performance of the ear muffs.

Your supplier can give you information about spare parts and further maintenance. These models of ear-muffs have satisfied the optional requirements at -20 to +50 °C. The headset should be stored indoors at normal room temperature protected from dust and moisture. For long time storage please remove the batteries.

Operation of the communication unit

This headset can communicate, in full duplex, with other units working on the Bluetooth protocol (another Bluetooth headset or mobile phones with Bluetooth interface). You need to install two AA batteries (LR6 or HR6) in the battery slot before use. Rechargeable batteries (HR6) in combination with a charger are recommended. Under full duplex communication a pair of batteries will last for about 10 hours depending on the quality of the batteries. Warning: Do not try to re-charge any other batteries than recommended from the battery supplier. It may explode.

The headset has two buttons. One ON/OFF-Volume switch and one function button (the smallest). A green led will be lit when the headset is turned ON.

The ON/OFF-Volume button works as ON/OFF switch by pressing only the central part of the button in, with your fingertip. The same button also acts as a volume control by turning the knob (clockwise for increasing volume and

counter clockwise for lower volume). The function button (the smallest) may have additional features on different headset models. The normal situation is that one click on the function button will mute the mic. You will then hear

a confirmation beep. To take the headset back to normal operation one additional click on the button will make the microphone work normal again. On aviation editions the function button will work as a PTT button for SIMPLEX communication.

Pairing two headsets

Every Bluetooth device is made for working in pairs. To pair two headsets you have to follow this procedure: Keep the headsets on your head or hold it so you can hear the loudspeakers during the process.

Push in the ON/OFF switch and the function button/mute mic and hold it depressed. You will receive one polyphonic “beep” to indicate that the headset is ON. After a few seconds you will hear the first pairing “beep”. Wait for about 3 seconds and you will hear the second pairing “beep”. Then you shall release both the buttons at the same time. You can now see that the LED is blinking rapidly which indicates seeking mode.

Within 30 seconds you need to pair the other headset into Headset mode.

This is done by carrying out the same procedure as the Radio Gateway headset but you have to release the ON/OFF switch and the function button after just ONE pairing “beep”. After about 5 seconds you will notice that the headsets have paired up and you can enjoy a full duplex communication between the two headsets. You can now turn the headsets off and on again without any new pairing next time you want to use them. For turning on an off after pairing it is only necessary to use the on/switch. In paired mode the LED will blink slowly. During a full duplex communication you are able to mute the microphone by pushing the function button once. The microphone will be muted until you push the function button once again.

Pairing a headset to a Bluetooth mobile phone

Make a Radio Gateway of one headset using the procedure described under “Pairing two headsets”. See the user manual for your mobile phone and carry out the procedure for pairing your phone to a Bluetooth headset. Wait until the mobile phone has found the headset. A headset symbol and the text “Free2move” will be showed in the display. You will now be asked for a PIN code from your mobile phone. Enter the PIN code 0000 on your phone and confirm.

You will now have a connection between your headset and the mobile phone. This allows you to answer your mobile phone from the headset. You will hear the ringing tone in the headset and you can answer and even end calls by pushing the function button once. If you have voice control on your mobile phone you can operate this from the headset as well. Push the function button and speak directly to the phones voice control. End calls by pushing the function button again. Be certain that the mobile phone is not moved more than 10 m. from the headset. The Bluetooth modules in mobile phones have normally a very limited range. The pairing to a mobile phone will last until you pair the headset to another Bluetooth device.

Sound attenuation AK6591

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean att. (dB)	16.3	19.5	28.6	36.4	32.2	39.2	39.2	42.6	41.0
St. dev.	3.1	2.6	4.3	3.2	2.2	3.7	3.3	4.1	4.8
APV (84%)	13.2	16.9	24.3	33.3	30.0	35.5	35.9	38.5	36.2

H₈₄ = 33 dB, M₈₄ = 27 dB, L₈₄ = 19 dB, SNR₈₄ = 29 dB. Standard weight for AK6591: 346 g.

Sound attenuation AK6592

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean att. (dB)	13.3	19.5	29.3	32.6	31.5	37.6	38.7	41.5	39.3
St. dev.	2.3	3.5	3.2	4.3	3.0	3.7	4.6	3.7	4.7
APV (84%)	11.1	16.0	26.1	28.3	28.5	33.8	34.1	37.8	34.6

H₈₄ = 31 dB, M₈₄ = 26 dB, L₈₄ = 18 dB, SNR₈₄ = 28 dB. Standard weight for AK6592: 317 g.