

PELTOR™

The Sound Solution

NEW

Easy Communication



3M™ Peltor™ LiteCom Safe noise reduction, effective communication

Communicating in noisy environments has never been easier – or safer. LiteCom is a tough and rugged headset designed to cope with demanding use in many different working environments. The cord-free two-way radio allows a two-way conversation on up to 8 channels, 38 subchannels, and has a range of up to 3,000 meters. It lets you talk hands-free and work safely regardless of harmful noise levels.



Built in two-way radio



www.3M.com/PeltorComms

3M



The importance of wearing hearing protection 100% of time exposed



100% usage

Gives the expected protection.



99% usage

Just five minutes of carelessness per day significantly reduces the effect of the hearing protector.



90% usage

Virtually no protection.

Safety

To be effective, a hearing protector should be used 100% of the time in noisy environments. Even taking it off for a short time dramatically reduces its effectiveness and greatly increases the risk of hearing damage. The two-way radio solutions in the LiteCom series encourage longer use because the wearer feels less isolated and can communicate with others more easily.

Convenient hearing protection

A hearing protector only provides protection when you are wearing it, so all settings and controls are designed to be intuitively simple, to avoid the need to remove the headset unnecessarily. A voice guides you through the menu. The headset switches itself off automatically if it is inactive for more than two hours, to conserve the battery. You are notified of battery status every time you switch the headset on.

Connect automatically

As soon as you talk into the microphone the chosen channel is opened in milliseconds, so other users can hear you regardless of the noise level, in the same seamless way. The microphone software is programmed only to pick up speech and effectively filters out all other sounds.



Specifications

Frequency range:	446 MHz (PMR)
Channels:	max 8 (PMR)
Subchannels:	38
Microphone type:	Noise cancelling Electret (MT53)
Output power:	150 mW
Range:	Up to 3 km depending on conditions
Battery type:	2 AA alkaline (3.0V) or NiMH (2.4V)
Operating time:	20 hours
Operating temperature:	-20°C to +55°C
Storage temperature:	-40°C to +55°C
Attenuation (SNR):	Headband: 32dB Helmet attachment: 33dB Neckband: 32 dB
Weight (incl. batteries):	394 g (headband), 418 g (helmet att.), 384 g (neckband)

Articles & Accessories

Description	3M art no
MT53H7A4400-EU LiteCom, PMR 446, headband	XH001680434
MT53H7P3E4400-EU LiteCom, PMR 446, helmet attachment	XH001680442
MT53H7B4400-EU LiteCom, PMR 446, neckband	XH001680459
HY79 Hygiene kit	XH001651047
ACK053 Rechargeable battery	XH001680608
FR08 Power supply	XH001680194
FR09 Battery charger	XH001680616
MT53N-12 Electret microphone	XL001633814
1180 SV Battery cover	XL001600565
HY100A Single-use protectors	XH001651351
HYM1000 Microphone protector	XH001651328
M995 Wind shield for electret microphone	11003066252



3M Personal Safety Division

3M Svenska AB, Box 2341
SE-331 02 Värnamo
Sweden

Phone: +46 (0) 370 65 65 65

Fax: +46 (0) 370 65 65 99

Internet: www.3M.com/Peltorcomms

Please recycle. Printed in Sweden.

© 3M 2013. All rights reserved.