

IPC2 i3 Barebone specifications

IPC2 i5 Barebone specifications

IPC2 i7 Barebone specifications

Retrieved on September 30, 2014 from [www.fit-pc.com](http://www.fit-pc.com)

Model			
Name	IPC2 i3 Barebone	IPC2 i5 Barebone	IPC2 i7 Barebone
Part Number	IPC2-C4010-WACB-FMUSB3	IPC2-C4300-WACB-FMUSB3	IPC2-C4600-WACB-FMUSB3
Block Diagram	IPC2 Block Diagram	IPC2 Block Diagram	IPC2 Block Diagram
Current HW Revision	1.1	1.1	1.1
Long Term Availability	2020	2020	2016 <sup>6</sup>
Processor			
Type	Intel 4th Gen Core i3-4010U Processor (Haswell)	Intel 4th Gen Core i5-4300U Processor (Haswell)	Intel 4th Gen Core i7-4600U Processor (Haswell)
Cores	64-bit dual core	64-bit dual core	64-bit dual core
Clock speed	1.7GHz	1.9GHz (turbo boost up to 2.9GHz)	2.1GHz (turbo boost up to 3.3GHz)
TDP	15W	15W	15W
Chipset	Intel Mobile Lynx Point LP PCH (MCP package)	Intel Mobile Lynx Point LP PCH (MCP package)	Intel Mobile Lynx Point LP PCH (MCP package)
Memory			
Supported	2x SO-DIMM 204-pin DDR3L SDRAM memory slots Up to 16GB (2x 8GB) DDR3L-1600 (1.35V only)	2x SO-DIMM 204-pin DDR3L SDRAM memory slots Up to 16GB (2x 8GB) DDR3L-1600 (1.35V only)	2x SO-DIMM 204-pin DDR3L SDRAM memory slots Up to 16GB (2x 8GB) DDR3L-1600 (1.35V only)
Installed	Not installed	Not installed	Not installed
Storage			
Supported	1x SATA up to 6 Gbps (SATA 3.0) for internal 2.5" HDD/SSD 1x mSATA slot up to 6 Gbps (SATA 3.0)	1x SATA up to 6 Gbps (SATA 3.0) for internal 2.5" HDD/SSD 2x mSATA slot up to 6 Gbps (SATA 3.0)	1x SATA up to 6 Gbps (SATA 3.0) for internal 2.5" HDD/SSD 2x mSATA slot up to 6 Gbps (SATA 3.0)
Installed	Not installed	Not installed	Not installed
Graphics			
GPU	Intel HD 4400 Graphics Triple display mode supported	Intel HD 4400 Graphics Triple display mode supported	Intel HD 4400 Graphics Triple display mode supported
Display Interface 1	HDMI 1.4a up to 4096 x 2304 @ 24 Hz	HDMI 1.4a up to 4096 x 2304 @ 24 Hz	HDMI 1.4a up to 4096 x 2304 @ 24 Hz
Display Interface 2	DisplayPort 1.2 up to 3200 x 2000 @ 60 Hz	DisplayPort 1.2 up to 3200 x 2000 @ 60 Hz	DisplayPort 1.2 up to 3200 x 2000 @ 60 Hz
Display Interface 3	HDMI 1.4a up to 4096 x 2304 @ 24 Hz	HDMI 1.4a up to 4096 x 2304 @ 24 Hz	HDMI 1.4a up to 4096 x 2304 @ 24 Hz
Audio			
Codec	Realtek ALC888-VC2 HD audio codec	Realtek ALC888-VC2 HD audio codec	Realtek ALC888-VC2 HD audio codec
Audio Output	Analog stereo output Digital 7.1+2 channels S/PDIF output 3.5mm jack	Analog stereo output Digital 7.1+2 channels S/PDIF output 3.5mm jack	Analog stereo output Digital 7.1+2 channels S/PDIF output 3.5mm jack
Audio Input	Analog stereo Microphone input Digital S/PDIF input 3.5mm jack	Analog stereo Microphone input Digital S/PDIF input 3.5mm jack	Analog stereo Microphone input Digital S/PDIF input 3.5mm jack
Networking			
LAN	2x GbE LAN ports LAN1: Intel I218 GbE PHY (MAC integrated into the chipset) (RJ-45) LAN2: Intel I211 GbE controller (RJ-45) LAN3-6: N/A	2x GbE LAN ports LAN1: Intel I218 GbE PHY (MAC integrated into the chipset) (RJ-45) LAN2: Intel I211 GbE controller (RJ-45) LAN3-6: N/A	2x GbE LAN ports LAN1: Intel I218 GbE PHY (MAC integrated into the chipset) (RJ-45) LAN2: Intel I211 GbE controller (RJ-45) LAN3-6: N/A
Wireless	WLAN 802.11ac (2.4/5GHz dual band Intel 7260HMMW) Bluetooth 4.0	WLAN 802.11ac (2.4/5GHz dual band Intel 7260HMMW) Bluetooth 4.0	WLAN 802.11ac (2.4/5GHz dual band Intel 7260HMMW) Bluetooth 4.0
Connectivity			
USB	4x USB 3.0 2x USB 2.0	4x USB 3.0 2x USB 2.0	4x USB 3.0 2x USB 2.0
Serial	3x Serial communication ports COM0: Full RS232 via mini serial connector COM1: 2-wire RS232 via mini serial connector COM3: 2-wire RS232 via mini serial connector	3x Serial communication ports COM0: Full RS232 via mini serial connector COM1: 2-wire RS232 via mini serial connector COM3: 2-wire RS232 via mini serial connector	3x Serial communication ports COM0: Full RS232 via mini serial connector COM1: 2-wire RS232 via mini serial connector COM3: 2-wire RS232 via mini serial connector
SD	N/A	N/A	N/A
Special I/O	1x micro SIM slot (6 pins) <sup>4</sup>	1x micro SIM slot (6 pins) <sup>4</sup>	1x micro SIM slot (6 pins) <sup>4</sup>
Expansion	Half-size mini-PCIe socket Full-size mini-PCIe/mSATA socket <sup>2</sup>	Half-size mini-PCIe socket Full-size mini-PCIe/mSATA socket <sup>2</sup>	Half-size mini-PCIe socket Full-size mini-PCIe/mSATA socket <sup>2</sup>
Advanced Technologies			
vPRO	No	Yes (Intel vPRO Technology) <sup>5</sup>	Yes (Intel vPRO Technology) <sup>5</sup>
AMT	No	Yes (Intel Active Management Technology) <sup>5</sup>	Yes (Intel Active Management Technology) <sup>5</sup>
CPU Virtualization	Yes	Yes	Yes
Special Functionality	Auto-On Wake-on-LAN Wake-on-Timer PXE Boot Watchdog	Auto-On Wake-on-LAN Wake-on-Timer PXE Boot Watchdog	Auto-On Wake-on-LAN Wake-on-Timer PXE Boot Watchdog

Bootloader			
Vendor	Phoenix	Phoenix	Phoenix
Features	BIOS Legacy mode UEFI 2.2 mode Secure Boot	BIOS Legacy mode UEFI 2.2 mode Secure Boot	BIOS Legacy mode UEFI 2.2 mode Secure Boot
Operating System			
Supported	Windows 7/8, 32-bit and 64-bit Windows Server 2012 R2 Linux 32-bit and 64-bit Embedded OS	Windows 7/8, 32-bit and 64-bit Windows Server 2012 R2 Linux 32-bit and 64-bit Embedded OS	Windows 7/8, 32-bit and 64-bit Windows Server 2012 R2 Linux 32-bit and 64-bit Embedded OS
Installed	Not installed	Not installed	Not installed
Operating Conditions			
Input Voltage	Unregulated 10 – 15VDC input <sup>1</sup>	Unregulated 10 – 15VDC input <sup>1</sup>	Unregulated 10 – 15VDC input <sup>1</sup>
Power Consumption	6W – 24W	6W – 24W	6W – 24W
Operating Temperature	1. Commercial HDD models: 0°C – 50°C SSD models: 0°C – 70°C 2. Extended (TE) SSD models only: -20°C – 70°C 3. Industrial (TI) SSD models only: -40°C – 70°C	1. Commercial HDD models: 0°C – 50°C SSD models: 0°C – 70°C 2. Extended (TE) SSD models only: -20°C – 70°C 3. Industrial (TI) SSD models only: -40°C – 70°C	1. Commercial HDD models: 0°C – 50°C SSD models: 0°C – 70°C 2. Extended (TE) SSD models only: -20°C – 70°C 3. Industrial (TI) SSD models only: -40°C – 70°C
Enclosure			
Material	Die Cast Aluminum	Die Cast Aluminum	Die Cast Aluminum
Cooling	Passive Cooling Fanless Design	Passive Cooling Fanless Design	Passive Cooling Fanless Design
Dimensions	19cm x 16cm x 4cm	19cm x 16cm x 4cm	19cm x 16cm x 4cm
Weight	1050gr	1050gr	1050gr
Package			
In the Box	1. Intense PC2 computer 2. Power supply: input 100-240VAC 50/60Hz, 60W output 12VDC 5A, DC plug lock, attachable NA and EU plugs 3. Video HDMI to DVI adapter 4. Audio 3.5mm to RCA cable 5. WiFi 2.4GHz/5GHz band 2 antennas (in some models) 6. Mini-serial to DB9-male adapter cable	1. Intense PC2 computer 2. Power supply: input 100-240VAC 50/60Hz, 60W output 12VDC 5A, DC plug lock, attachable NA and EU plugs 3. Video HDMI to DVI adapter 4. Audio 3.5mm to RCA cable 5. WiFi 2.4GHz/5GHz band 2 antennas (in some models) 6. Mini-serial to DB9-male adapter cable	1. Intense PC2 computer 2. Power supply: input 100-240VAC 50/60Hz, 60W output 12VDC 5A, DC plug lock, attachable NA and EU plugs 3. Video HDMI to DVI adapter 4. Audio 3.5mm to RCA cable 5. WiFi 2.4GHz/5GHz band 2 antennas (in some models) 6. Mini-serial to DB9-male adapter cable
Warranty	5 years <sup>3</sup>	5 years <sup>3</sup>	5 years <sup>3</sup>
Notes	1. Nominal input voltage: 12V 2. Shared with mSATA 3. For products purchased since 1-Jan-2013 4. For use with mini PCIe Cellular Modem module	1. Nominal input voltage: 12V 2. Shared with mSATA 3. For products purchased since 1-Jan-2013 4. For use with mini PCIe Cellular Modem module 5. Supported on LAN1 only	1. Nominal input voltage: 12V 2. Shared with mSATA 3. For products purchased since 1-Jan-2013 4. For use with mini PCIe Cellular Modem module 5. Supported on LAN1 only 6. The product will be available after 2016 with similar or better CPU