

XG C-C1 – software configurable RSM with superior audio quality



Designed for following uses and industries



KEY BENEFITS

- 2 large programmable PTT buttons
- Status LED for added safety
- Easy to use, excellent tactile feeling
- Connections to bone conductive headsets
- Volume up/down button
- Programmable Smart PTT – alternates between standard PTT and Smart PTT
- Wireless PTT
- Audio routing button - mutes/unmutes internal speaker when headset is connected
- Emergency button, programmable
- Microphone sensitivity control. User configurable, possibility to revert to default settings

Play product video:



Built to military standard, the Savox XG C-C1 is a new remote speaker microphone designed for ease of configuration and superior audio in high noise environments. The XG C-C1 highlights include adjustable microphone sensitivity to help you to cut out the noise, max sized buttons ensure for easy use even with gloved hands and a programmable Smart PTT to keep both hands free when working.

Note the new SAVOX QR5 rugged quick release connector for headsets as well as a 3,5mm earphone jack connector and status LED for added safety. Rounding up the package, a complete range of compatible headsets and earphones.

Standard black and high-viz yellow versions available.

TECHNICAL DATA

| | |
|--------------------------------------|---|
| WEIGHT | 170g without radio connector cable |
| SIZE | 115mm x 70mm x 38mm |
| MATERIAL | Polyamide |
| COLOR OPTIONS | Black housing with red PTT buttons and safety yellow housing with black PTT buttons |
| FIXING | Rugged 360° rotating clothing clip |
| SUPPLY VOLTAGE | 3-10VDC, powered from radio |
| CONNECTIONS | Savox QR5 rugged quick release connector for headsets. Earphone 3,5mm jack connector |
| CURRENT DRAIN | 6mA @ idle state |
| SPEAKER | 8 Ohm, max 2W, SPL 90dB / 0,5W / 0,2m |
| MICROPHONE | Omni directional, sensitivity -39dB ± 2dB |
| OPERATIONAL TEMPERATURE | -40...+85°C |
| STORAGE TEMPERATURE | -40...+85°C |
| INGRESS PROTECTION | IP67 and MIL-STD-810G, procedure 1 |
| ELECTROMAGNETIC COMPATIBILITY | Emissions, EN 300 394-1 / Immunity, EN 301 489-1 and EN 301 489-18 / Radiated, EN 61000-4-3 / ESD, EN 61000-4-2 |